Renovation Recordkeeping Checklist

Date and Location of Renovation: Brief Description of Renovation: Name of Assigned Renovator: Name(s) of Trained Worker(s), if used: Copies of renovator and dust sampling technician qualifications (training certificates, certifications) on file Certified renovator provided training to workers on (check all that apply): Posting warning signs Setting up plastic containment barriers Maintaining containment Avoiding spread of dust to adjacent areas Waste handling Post-renovation cleaning Test kits used by certified renovator to determine whether lead was present on components affected by renovation (identify kits used and describe sampling locations and results): Warning signs posted at entrance to work area. Work area contained to prevent spread of dust and debris All objects in the work area removed or covered (interiors) HVAC ducts in the work area closed and covered (interiors) Windows in and within 20 feet of the work area closed (exteriors) Doors in the work area closed and sealed (interiors) Doors that must be used in the work area covered to allow passage but prevent spread of dust Floors in the work area covered with taped-down plastic (interiors)
Name of Assigned Renovator: Name(s) of Trained Worker(s), if used: Name of Dust Sampling Technician,
Name of Dust Sampling Technician, Inspector, or Risk Assessor, if used: Copies of renovator and dust sampling technician qualifications (training certificates, certifications) on file Certified renovator provided training to workers on (check all that apply): Posting warning signs
Name of Dust Sampling Technician, Inspector, or Risk Assessor, if used: Copies of renovator and dust sampling technician qualifications (training certificates, certifications) on file Certified renovator provided training to workers on (check all that apply): Posting warning signs Setting up plastic containment barriers Maintaining containment Avoiding spread of dust to adjacent areas Waste handling Post-renovation cleaning Test kits used by certified renovator to determine whether lead was present on components affected by renovation (identify kits used and describe sampling locations and results): Warning signs posted at entrance to work area. Work area contained to prevent spread of dust and debris All objects in the work area removed or covered (interiors) HVAC ducts in the work area closed and covered (interiors) Windows in the work area closed (interiors) Doors in the work area closed and sealed (exteriors) Doors in and within 20 feet of the work area closed and sealed (exteriors) Doors that must be used in the work area covered to allow passage but prevent spread of dust
Inspector, or Risk Assessor, if used: Copies of renovator and dust sampling technician qualifications (training certificates, certifications) on fill Certified renovator provided training to workers on (check all that apply): Posting warning signs Setting up plastic containment barriers Maintaining containment Avoiding spread of dust to adjacent areas Waste handling Post-renovation cleaning Test kits used by certified renovator to determine whether lead was present on components affected by renovation (identify kits used and describe sampling locations and results): Warning signs posted at entrance to work area. Work area contained to prevent spread of dust and debris All objects in the work area removed or covered (interiors) HVAC ducts in the work area closed and covered (interiors) Windows in the work area closed (interiors) Windows in and within 20 feet of the work area closed (exteriors) Doors in the work area closed in the work area closed and sealed (exteriors) Doors that must be used in the work area covered to allow passage but prevent spread of dust
 Work area contained to prevent spread of dust and debris All objects in the work area removed or covered (interiors) HVAC ducts in the work area closed and covered (interiors) Windows in the work area closed (interiors) Windows in and within 20 feet of the work area closed (exteriors) Doors in the work area closed and sealed (interiors) Doors in and within 20 feet of the work area closed and sealed (exteriors) Doors that must be used in the work area covered to allow passage but prevent spread of dust

Client Name and title Date